

PRODUCT DATA SHEET



SRC #1 "S" SYNTHETIC ROLLER CHAIN

PRODUCT DESCRIPTION

SRC #1 Roller Chain "S" is a metallic roller chain lubricant with a high percentage of homogenized submicron particles self-lubricating metallic solids.

The carrier will act as a medium to carry the solids and deposit them into all internal working areas of the chains to guarantee maximum reduction of friction and subsequently elimination of wear.

The non-oily carrier will assure maximum cleanliness providing adequate corrosion protection and water displacement while acting as a rust and corrosion preventative.

DIRECTIONS: Shake can well before use. Can temperature should be 18°C (65°F) or warmer. (*WARNING: Never use direct heat to warm aerosol cans! ONLY warm water should be used!*) Spray part to be lubricated, repeating as necessary.

Sentinel's "S" line of spray lubricants is a non-ozone depleting product specially formulated for industry. Sentinel's "S" line contains no CFC's, HCFC's, Methyl chloroform, or any other material known to affect the stratospheric ozone.

TYPICAL CHARACTERISTICS

Viscosity cSt	@ 100°C	3.6	
	@ 40°C	13.7	ASTM D- 445
Viscosity Index		144	ASTM D-2270
Pour Point °C (°F)		-48 (-50°F)	ASTM D- 97
Flash Point °C (°F)		120 (248°F)	ASTM D- 92
Fire Point °C (°F)		133 (271°F)	ASTM D- 92
Foam Sequence I, II, III		Nil	ASTM D- 892
Demulsibility, 82°C		Pass	ASTM D-1401
Copper Corrosion, 121°C (250°F)			
3 Hours		1a	ASTM D- 130
Rust Test		Pass	ASTM D-665 A&B
Solids		Molybdenum Disulfide	
Appearance		Light Gray	
USDA Classification		H-2	
Net Weight per 20oz Aerosol Can		15 oz. (425g)	

PIN #

01019

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240
15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565
WWW.SENTINELSYNTHETIC.COM