

PRODUCT DATA SHEET



SL-WPG WATERPROOF GREASE

PRODUCT DESCRIPTION

SL-WPG is outstanding synthetic lubricating grease for every phase of lubrication. Its performance is exceptional in the presence of water though definitely not limited to this type of application. It cannot be washed out, even when subjected to high rpm, boiling waters and extreme temperatures under 204°C (400°F).



SL-WPG has superior tenacity and is heavy-bodied; it clings tenaciously to metal surfaces. It will not pound out, sling out, dissolve out, or melt out.

SL-WPG is recommended for all types of bearings, slides, cams, and in all types of mechanical equipment subjected to water and or salt conditions at any temperature range from -28°C (-20°F) to 227°C (440°F).

TYPICAL CHARACTERISTICS

NLGI Grade	2	ASTM D-1092
Worked Penetration	265-295	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability Psi drop @ 100 hrs	-1	ASTM D- 942
Rust Preventative No Stain	1a	ASTM D-1743
Water Washout	.4	ASTM D-1264
Extreme Pressure Timken OK Load Kg (Lb)	34+ (75)	ASTM D-2509
Four Ball Wear	.6 mm	ASTM D-2266
Solids	MoS ₂	
Food Grade Status	H2	NSF
NSF Registration	137132	
Appearance	Blue Green Stringy	
PIN #		03090

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240
15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565
WWW.SENTINELSYNTHETIC.COM