

PRODUCT DATA SHEET



ANTI-SEIZE EXTREME PRESSURE

PRODUCT DESCRIPTION

Sentinel's Anti-Seize is a synthetic multi-purpose E.P. Lubricant. It may be used in production machinery (sliding surfaces of reciprocating parts), machine shops, tool and die manufacturing, chemical industry applications, metal working and general industry. Sentinel's Anti-Seize will prevent corrosion and provide excellent lubrication on parts exposed to water, steam and most acids or alkalis.

Sentinel's Anti-Seize is a highly concentrated, stable, non-melting molybdenum disulfide compound. It is impervious to water and is not affected by most acids or alkalis.

Sentinel's Anti-Seize has excellent lubricating qualities from -150°C (-300°F) to over 954°C (1750°F). It has a high film strength, low coefficient of friction and a tenacious adherence to metal surfaces.

Sentinel's Anti-Seize reduces wear and prevents seizing and galling on all extreme applications.

TYPICAL CHARACTERISTICS

NLGI Grade	3	ASTM D-1092
Worked Penetration	220-250	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability Psi Drop @ 100 hrs	-1	ASTM D- 942
Rust Preventative	1a	ASTM D-1743
Water Washout	0.8	ASTM D-1264
Extreme Pressure Timken OK Load Kg (Lb)	50+ (110)	ASTM D-2509
Four Ball Wear	.5mm	ASTM D-2266
Solids	MoS ₂	
USDA Rating	H-2	
Appearance	Dark Metallic	

PIN #

03193

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240
15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565
WWW.SENTINELSYNTHETIC.COM