

MATERIAL SAFETY DATA SHEET

MSDS FORMAT MEETS ANSI Z400.1-1993 AND OSHA 1910.1200



SENTINEL'S CITRA-SOLV

REVISION# 1

MSDS #

REVISION DATE: JANUARY 2, 2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Sentinel's Citra Solv

PRODUCT NUMBER (S): 02320

SYNONYM: Sentinel's Citra-Solv

COMPANY IDENTIFICATION

Sentinel Lubricants Corp.
15755 N.W. 15th Ave.
Miami, FL 33169

EMERGENCY TELEPHONE NUMBERS

HEALTH (24 hr) : (800) 842-6400 or (305) 625-6400
TRANSPORTATION (24 hr) : (800) 842-6400
or (305) 625-6400 Int'l collect calls accepted

PRODUCT INFORMATION:

MSDS Requests: (800) 842-6400
Environmental, Safety, & Health Info: (800) 842-6400
Product Information: (800) 842-6400

2. COMPOSITION/INFORMATION ON INGREDIENTS

100% SENTINEL'S CITRA-SOLV

CONTAINING

COMPONENTS	AMOUNT	LIMIT/QTY	AGENCY/TYPE
------------	--------	-----------	-------------

CYCLOHEXENE			
Chemical Name: Cyclohexene			
CAS5989275			

COMPOSITION COMMENT

All the components of this material are in the Toxic Substances Control Act Chemical Substances Inventory.

This product fits the ACGIH definition for mineral oil mist. The ACGIH TLV is 5 mg/m³, the OSHA PEL is 5mg/m³.

3. HAZARD IDENTIFICATION AND EMERGENCY AND FIRST AID PROCEDURES

POTENTIAL HEALTH EFFECTS

EYE:

Not expected to cause prolonged or significant eye irritation.

SKIN

Contact with skin is not expected to cause prolonged or significant irritation. Not expected to be harmful to internal organs if absorbed through the skin. High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but if left untreated could result in disfigurement or amputation of the affected part.

INGESTION

Not expected to be harmful if swallowed.

INHALATION

Contains a synthetic-based oil that may cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended exposure limit.

4. FIRST AID MEASURES

EYE:

No specific first aid measures are required because this material is not expected to cause eye irritation. As a precaution remove contact lenses if worn, and flush eyes with water.

SKIN

No specific first aid measures are required because this material is not expected to be harmful if it contacts the skin. As a precaution, remove clothing and shoes if contaminated. Use a waterless hand cleaner, mineral oil, or petroleum jelly to remove the material. Then wash skin with soap and water. Wash or clean contaminated clothing and shoes before reuse.

INGESTION

No specific first aid measures are required because this material is not expected to be harmful if swallowed. Do not induce vomiting. As a precaution, give the person a glass of water or milk to drink and get medical advice. Never give anything by mouth to an unconscious person.

INHALATION

If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

NOTE TO PHYSICIANS

In an accident involving high-pressure systems, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

5. FIRE FIGHTING MEASURES

SPECIAL NOTES:

Leaks/ ruptures in high-pressure systems using materials of this type can create a fire hazard when in the vicinity of ignition sources (e.g. Open flame, pilot lights, sparks, or electric arcs).

FLASH POINT (TCC) 46°C (115°F) Min. of solvent portion.

AUTOIGNITION: NDA

FLAMMABILITY LIMITS (% by volume in air): Lower: 0.7% UPPER: 6.1 of solvent portion

EXTINGUISHING MEDIA: CO2, Dry Chemical, Foam, Water Fog

NFPA RATINGS: Health 1; Flammability 1; Reactivity; 0.

FIRE FIGHTING INSTRUCTIONS:

This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

COMBUSTION PRODUCTS:

Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

EMERGENCY NUMBER (24hr) : (800) 842-6400 or (305) 625-6400, International Collect Calls Accepted.

ACCIDENTAL RELEASE MEASURES:

Stop the source of the leak or release. Clean up releases as soon as possible. Contain liquid to prevent further contamination of soil, surface water or leading to surface water or groundwater. Clean up small spills using appropriate techniques such as absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.

Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

This material does not contain any CERCLA Hazardous Substances.

This material does not contain any SARA Title III Section 302 – Extremely Hazardous Substances.

This material does not contain any SARA Title III Section 313 – Toxic Chemicals.

7. HANDLING AND STORAGE

DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Drum is not designed to contain pressure. Do not use pressure to empty drum or drum may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty drums should be completely drained, properly bunged, and promptly returned to a drum re-conditioner, or properly disposed of. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATION

Consider the potential hazards of this material (see section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS

Use in a well-ventilated area. If user operations generate an oil mist, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended mineral exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Where splashing is possible, wear safety glasses with side shields as a good safety practice.

EYE PROTECTION:

No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

SKIN PROTECTION:

No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances. Suggested materials for protective gloves include: <Viton> <Nitrile> <Silver Shield>

RESPIRATORY PROTECTION

No respiratory protection is normally required. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not wear an approved respirator that provides adequate protection from the measured concentrations of this material. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES**PHYSICAL DESCRIPTION:**

Clear to Yellow Cast, Light Fluid, Orangey

pH:	NDA
VAPOR PRESSURE:	2 mm Hg
VAPOR DENSITY (AIR = 1):	NA
BOILING POINT:	NA
FREEZING POINT:	NA
MELTING POINT:	NA
SOLUBILITY:	Soluble in water
SPECIFIC GRAVITY:	0.83 – 0.84 @ 25°C
EVAPORATION RATE:	Less than 1
VISCOSITY:	Water Thin
PERCENT VOLATILE (VOL):	75%

10. STABILITY AND REACTIVITY**HAZARDOUS DECOMPOSITION PRODUCTS:**Smoke may be acrid and fume irritating. Burning generates CO, CO₂ and smoke. Product is not an oxygen donor.**CHEMICAL STABILITY:**

Stable.

CONDITIONS TO AVOID:

Excessive Heat

INCOMPATIBILITY WITH OTHER MAETERIALS:

May react with strong oxidizing agents and acidic agents, including acidic clays, peroxides, halogens, vinyl chloride and iodine penta fluoride.

HAZARDOUS POLYMERIZATION:

Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:

The eye irritation hazard is based on data for a similar material.

SKIN EFFECTS:

The skin irritation hazard is based on data for a similar material.

EYE EFFECTS:

The eye irritation hazard is based on data for a similar material.

SKIN EFFECTS:

The skin irritation hazard is based on data for a similar material.

ACUTE ORAL EFFECTS:

The acute oral toxicity is based on data for a similar material.

ACUTE INHALATION EFFECTS:

The acute respiratory toxicity is based on data for a similar material.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

No data available.

ENVIRONMENTAL FATE:

This material is considered inherently biodegradable. Small accidental leaks or releases of this material are not expected present an environmental problem. See section 6 for Accidental Release Measures.

13. DISPOSAL CONSIDERATIONS

Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods

14. TRANSPORTATION AND OSHA RELATED LABEL INFORMATION

The description shown may not apply to all shipping situations. Consult 49 CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT SHIPPING NAME: NOT DESIGNATED AS A HAZARDOUS MATERIAL BY THE FEDERAL DOT
 DOT HAZARD CLASS: NOT APPLICABLE
 DOT IDENTIFICATION NUMBER: NOT APPLICABLE
 DOT PACKING GROUP: N/A

ADDITIONAL INFORMATION: Lubricating Oil, N.O.I.B.N. – Not hazardous by U.S. DOT.
 ADR/RID Hazard Class – Not Applicable

15. REGULATORY INFORMATION

SARA 311 CATEGORIES:

- | | |
|---------------------------------------|----|
| 1. Immediate (Acute) Health Effects: | NO |
| 2. Delayed (Chronic) Health Effects: | NO |
| 3. Fire Hazard: | NO |
| 4. Sudden Release of Pressure Hazard: | NO |
| 5. Reactivity Hazard: | NO |

REGULATORY LISTS SEARCHED:

01=SARA 313	11=NJ RTK	22=TSCA Sect 5(a) (2)
02=MASS RTK	12=Cercla 302.4	23=TSCA Sect 6
03=NTP Carcinogen	13=MN RTK	24=TSCA Sect 12 (b)
04=CA Prop 65-Carcin	14=ACGIH TWA	25=TSCA Sect 8 (d)
05=CA Prop 65-Repro Tox	15=ACGIH STEL	26=TSCA Sect 8 (a)
06=IARC Group 1	16=ACGIH Calc TLV	27=TSCA Sect 4 (a)
07=IARC Group 2A	17=OSHA PEL	28=Canadian WHMIS
08=IARC Group 2B	18=DOT Marine Pollutant	29=OSHA CEILING
09=SARA 302/304	19=Sentinel TWA	30=Sentinel STEL
10=PA RTK	20=EPA Carcinogen	

The following components of this material are found on the regulatory lists indicated.

EU RISK AND SAFETY LABEL PHRASES:

May cause long-term adverse effects in the aquatic environment

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A.

34:5A-1 et. Seq., the product is to be identified as follows:

PETROLEUM OIL

WHMIS CLASSIFICATION:

This product is not considered a controlled product according to the criteria of the Canadian Controlled Products Regulations.

16. OTHER INFORMATION

NFPA RATINGS: Health 1; Flammability 1; Reactivity 0;

HMIS RATINGS: Health 1; Flammability 1; Reactivity 0;

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator).

These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (For HMIS ratings)

REVISION STATEMENT:

This is a new Material Safety Data Sheet.

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV	-	Threshold Limit Value	TWA	-	Time Weighted Average
STEL	-	Short-term Exposure Limit	TPQ	-	Threshold Planning Quantity
RQ	-	Reportable Quantity	PEL	-	Permissible Exposure Limit
C	-	Ceiling Limit	CAS	-	Chemical Abstract Service Number
A1-5	-	Appendix A Categories	()	-	Change Has Been Proposed
NDA	-	No Data Available	NA	-	Not Applicable

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1)

The above information is based on the data of which we are aware and is believed to be correct as of data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date. Hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.