

PRODUCT DATA SHEET



SL-SR-33 SOLVENT RESISTANT GREASE

PRODUCT DESCRIPTION

A fully synthetic solvent resistance grease for all types of bearings operating under extreme chemical attack. Totally resistant to kerosene, naphtha, perchlorethlene, mineral oils and most all types of hydrocarbon solvents.

Good protection against carbon tetrachloride, xylene. Useable good rust and oxidation protective film. Used in many chemical industries.

TYPICAL CHARACTERISTICS

NLGI Grade	2 ½	ASTM D-1092
Worked Penetration	250-275	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability		
Psi drop @ 100 hrs	-1	ASTM D- 942
Rust Preventative	1a	ASTM D-1743
No Stain		
Water Washout	1	ASTM D-1264
Extreme Pressure	34+ (75)	ASTM D-2509
Timken OK Load Kg (Lb)		
Four Ball Wear	.6 mm	ASTM D-2266
Appearance	Amber	

PIN #

03001

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240
15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565
WWW.SENTINELSYNTHETIC.COM