

PRODUCT DATA SHEET



SL-RCG RUBBER COMPATIBLE GREASE

PRODUCT DESCRIPTION

SL-RCG is rubber compatible grease specifically formulated and designed to operate as multi-purpose grease without having the usual effects that grease have when in contact with rubber seals and "O" rings.

It is completely compatible with the following rubber materials: natural, Buna S, Buna N, and neoprene.

Effects on Rubber 5 Days (120 hrs.) @ 158°F

	Natural	Buna S	Buna N	Butyl	Neoprene
% Linear Swell	0.35	0.7	0.7	1.5	0.0
Hardness	-2	-2	+2	+4	-2
Operating Range				-50 to +325	
Color				Light Tan	

TYPICAL CHARACTERISTICS

NLGI Grade	2	ASTM D-1092
Worked Penetration	265-295	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability Psi drop @ 100 hrs	-1	ASTM D- 942
Rust Preventative No Stain	1a	ASTM D-1743
Water Washout	1	ASTM D-1264
Extreme Pressure Timken OK Load Kg (Lb)	34+ (75)	ASTM D-2509
Four Ball Wear	.6 mm	ASTM D-2266
Appearance	Light Tan	

PIN #

03010

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240
15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565
WWW.SENTINELSYNTHETIC.COM