

PRODUCT DATA SHEET



PRIMO SPONTANEOUS EMULSIFIER

PRODUCT DESCRIPTION

From the original, patented non-butyl technology comes another first in industrial cleaning efficiency. This product has been extensively field-tested in heavy-duty industrial types of mechanical cleaning devices.

CLEANS by spontaneous emulsion. Reduces the resistance of oily and greasy soil to mix with water. **BUILT** with extra alkaline punch. **SPECIAL ELECTROLYTES** to enhance the action of the surfactant. **DISPERSES** solids soil. **STABLE EMULSION** prevents redeposition of oily soils during cleaning. **FORMULATED** with special water conditioning properties. **INHIBITED** against attack on all metal surfaces. **RETARDS** corrosion even after cleaning. **BRIGHTENS** weathered aluminum truck bodies. Contains no butyls or other toxic solvents.

PHYSICAL AND PERFORMANCE REQUIREMENTS

USE: To remove oil, greasy soil from all types of hard surfaces. For use in mechanical cleaning devices in industrial locations and utility areas of commercial and institutional buildings. Also for use in truck cleaning

DIRECTIONS:

FOR USE IN AUTOMATIC SCRUBBERS: Increase strength of dilution enough to remove oil present. 20 to 1 dilution with water is recommended.

FOR STEAM CLEANING: To the concentrate solution tank, mix 4 to 14 ounces with each gallon of water. Adjust the solution tank valve to obtain amount of cleaner devices in industrial locations and utility areas of commercial and institutional building. Also for use in truck cleaning.

FOR SOAK IN TANK OR ULTRASONICS: This product can be used at 12 ounces per gallon of water.

FOR SPRAY CLEANING: Prepare solution and apply by spray to surface. 20 to 1 dilution with water for normal cleaning. To clean and brighten weathered aluminum surfaces at 10 to 1 dilution with water is recommended

TYPICAL CHARACTERISTICS

Flash Point	None
PH (as supplied)	13.0 Min
Solvent Content	None
Butyl Cellosolve Content	None
Other Glycol Ether Content	None
Foam Properties	Low Foam (fast break)
Solubility	Infinite
Surfactant System	Non-ionic
Wt./Gallon	8.76
Appearance	Blue
Odor	Sassafras
USDA Rating	A1
PIN #	02230

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.

P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240

15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603

PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565

WWW.SENTINELSYNTHETIC.COM