

## PRODUCT DATA SHEET



### **CITRA-SOLV** **ALL NATURAL CLEANER AND** **DEGREASER**

#### PRODUCT DESCRIPTION

Sentinel's Citra-Solv is a heavy duty cleaner and degreaser that will remove dirt, oil and grease from surface easily. Citra-Solv is all natural, biodegradable, water risible, non-toxic.

Citra-Solv is used to clean knives, saw blades, tools equipment, tables, painted surfaces, conveyers, hard surfaces, machinery, industrial equipment, materials handling equipment, and electric motors.

#### TYPICAL CHARACTERISTICS

Specific Gravity, g/cc @ 60/60°F	0.85
Flash Point, °C (°F)	46 (115)
Boiling Point, °C (°F)	154 (310)
Acid Number, mg KOH/g	0.14
Kauri Butanol Value	62.7
Weight/ lbs/gal @ 21°C (70°F)	7.1
Refractive Index	1.4711
Odor	Strong Citrus
Color	Clear to Yellow Cast

**PIN #** **02320**

#### TO ORDER OR FOR ADDITIONAL INFORMATION

### **QUALITY WITHOUT QUESTIONS!**

**SENTINEL LUBRICANTS CORP.**  
**P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240**  
**15755 NW 15<sup>TH</sup> AVENUE MIAMI, FLORIDA 33169-5603**  
**PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565**  
**WWW.SENTINELSYNTHETIC.COM**

## TECHNICAL DATA



## CITRA-SOLV ALL NATURAL CLEANER AND DEGREASER

### DIRECTIONS:

**TO CLEAN & DEGREASE SURFACES:** Dilute 4 oz. Into 1 gallon of warm water. Apply solution generously to surface to be cleaned. Let stand for 5 minutes. Rinse thoroughly.

**FOR ODOR CONTROL:** Dilute 2 oz. Into 1 gallon of cold water. Apply through a sprayer to odor source. Results in immediate fresh citrus scent.

**TO UNCLOG DRAINS:** Pour 8 oz. directly into drain. Let stand for 1 hour or more. Flush with hot water. For disposal, use same procedure.

### USED TO:

Degrease Trucks	Remove Decals
Unclog Grease	Clean Drains
Remove Printer's Ink	Remove Adhesive
Remove Tire Marks	Clean Motors
Remove Soap Scum	Clean Equipment
Detar Vehicles & Loosen Chewing Gum from Carpets & Hard Surfaces (other than plastic)	
Cleans Fuel Oil Deposits from Metal Surfaces	

100% Organic Formulation. 1 step degreasing and deodorizing. NON-CORROSIVE. Contains no Petroleum Distillates, Organic Halides or Alkalies – Will strip grease and heavy oil deposits from virtually any surface. Emulsifies instantly in water to penetrate and liquefy many different types of resins and greases.

**CAUTION: KEEP OUT OF REACH OF CHILDREN**

Combustible – Keep away from heat and open flame. Do not take internally. Avoid contact with eyes. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, consult a physician immediately. May be harmful to plastics or painted surfaces. **TEST SURFACE IN AN INCONSPICUOUS AREA BEFORE USING.** Because it is powerful grease solvent, it will defat skin. Use of rubber gloves are recommended to avoid chapped skin. Keep container tightly closed when not in use. For Commercial and Industrial Use only, or for sale to, use and storage by service persons.

### USED IN

Sewage Plants	Schools
Service Stations	Restaurants
Garbage Trucks	Office Buildings
Automotive Plants	Apartments
Theaters	Nursing Homes
Locker Rooms	Hospitals
Rest Rooms	Commissaries

## QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.  
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240  
15755 NW 15<sup>TH</sup> AVENUE MIAMI, FLORIDA 33169-5603  
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565  
WWW.SENTINELSYNTHETIC.COM

## TECHNICAL DATA



## CITRA-SOLV ALL NATURAL CLEANER AND DEGREASER

## COMPATIBILITY CHART

CPVC	No effect-Excellent
Epoxy	No effect-Excellent
Polypropylene	Moderate effect-Fair
Polyethylene	Moderate effect-Fair
PVC	Minor effect-Good
Cycolac (ABS) (Reg TM Borg-Warner Co.)	Minor effect-Good
Phenolic	No effect-excellent
Nylon	No effect-excellent
Noryl (Reg TM General Electric Co.)	UNKNOWN
Delrin (Acetal) (Reg TM E.I. du pont de Nemours & Co.)	Severe effect-Not Recommended
Ryton to 200°F (Reg TM Phillips Petroleum Co.)	UNKNOWN
Kynar (PVDF) (Reg TM Pennwalt Corp.)	No effect-Excellent
Teflon (Reg TM E.I. Dupont de Nemours & Co.)	No effect-Excellent
Stainless Steel (316)	No effect-Excellent
Stainless Steel (304)	No effect-Excellent
Stainless Steel (440)	No effect-Excellent
Titanium	No effect-Excellent
Carpenter 20	No effect-Excellent
Cast bronz	No effect-Excellent
Aluminum	No effect-Excellent
Hastelloy C	No effect-Excellent
Carbon/ceramic	No effect-Excellent
Ceramagnet A	No effect-Excellent
Viton (Reg TM E.I. du pont de Nemours & Co.)	No effect-Excellent
Burna N	No effect-Excellent
Neoprene	Moderate effect-Fair
Nitrile	No effect-Excellent
Natural Rubber	Moderate effect-Fair
Hypalon (Reg TM E.I. du pont de Nemours & Co.)	UNKNOWN
EPDM	UNKNOWN
Kel-F (Reg TM 3M Company)	UNKNOWN
Tygon (Reg TM Norton Co.)	Moderate effect-Fair
Silicone	Severe effect-Not recommended
Ceramic	No effect-Excellent
Carbon/graphite	No effect-Excellent

Recommended Gasket Material:

Man-holes use Viton®  
Pump parts use Teflon®  
O-Rings use Fluro-Silicon®  
Rubber gaskets must be periodically replaced

TO ORDER OR FOR ADDITIONAL INFORMATION

## QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.  
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240  
15755 NW 15<sup>TH</sup> AVENUE MIAMI, FLORIDA 33169-5603  
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565  
WWW.SENTINELSYNTHETIC.COM