

## PRODUCT DATA SHEET



# ELECTRO-SOLV "S"

## ELECTRIC / ELECTRONIC DEGREASER AND CLEANER

### PRODUCT DESCRIPTION

Electro-Solv "S" is a new non-ozone depleting cleaner and degreaser for electrical and electronic parts. Contains no CFC's, HCFC's, Methyl Chloroform, or any other material known to damage stratospheric ozone. Electro-Solv penetrates quickly, is fast evaporating, leaves no residue, is non-conductive and is safe for use on metals and plastics. Formulated specifically for cleaning electrical and electronic parts, equipment and other sensitive mechanisms. Electro-Solv penetrates into cracks and crevices to remove oils, grease, grim, flux, and other contaminants.

Use on tuners, tape heads, connectors, contacts, office equipment, printed circuits, switches, relays, controls, semi-conductors, breakers, and numerous applications.

- NON-CONDUCTIVE ●NO RESIDUE ●ODC FREE
- FAST EVAPORATION

**DIRECTIONS:** Can temperature should be 18°C (65°F) or warmer. (*WARNING: Never use direct heat to warm aerosol cans! Only warm water should be used!*) Insert plastic extender tube into spray tip for pinpoint control and elimination of over spray. Spray electrical equipment and allow 30 seconds for soil and other deposits to soften. Flush away soil with second spraying. *Allow to dry thoroughly before restarting or reusing equipment.*

Sentinel's "S" lines of spray lubricants are non-ozone depleting products specially formulated for industry. Sentinel's "S" line contains no CFC's, HCFC's, Methyl chloroform, or any other material known to affect the stratospheric ozone.

### TYPICAL CHARACTERISTICS

|                                   |                 |
|-----------------------------------|-----------------|
| Appearance                        | Clear liquid    |
| Flash Point, °C (°F)              | < -17 (0)       |
| Specific Gravity, g/cc @ 60/60°F  | 0.66            |
| Weight, lbs./gal @ 70°F           | 5.5             |
| ODC Content, % wt                 | None            |
| Surface Tension, dynes/cm @ 77 °F | 17.5            |
| Dielectric Strength, KV           | 35              |
| Propellant                        | CO <sub>2</sub> |
| USDA Classification               | H-2             |
| Kauri-Butanol Value               | 28              |
| Net Weight per 20oz Aerosol Can   | 14oz. (397g)    |
| <b>PIN #</b>                      | <b>01005</b>    |

### TO ORDER OR FOR ADDITIONAL INFORMATION

## QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.  
P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240  
15755 NW 15<sup>TH</sup> AVENUE MIAMI, FLORIDA 33169-5603  
PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565  
WWW.SENTINELSYNTHETIC.COM