

PRODUCT DATA SHEET



SLOG "S" OPEN GEAR COMPOUND

PRODUCT DESCRIPTION

Sentinel SL-OG "S" is a unique synthetic metallic compound designed for general purpose open gear lubrication. It has a high tacky content that prevents it from slinging out even at high RPM's. It is especially formulated to stay on exposed parts of gears, resisting extreme pressures from close moving parts. SL-OG "S" has a thermal range of from -40°C to 232°C (-40°F to 450°F) and an E.P. rating in excess of 150,000 P.S.I.

Sentinel SL-OG "S" has metallic particles incorporated into its synthetic carrier, making it bronze in color and giving it greater plating action. It can even be applied while equipment is running.

DIRECTIONS: Shake can well before use. Can temperature should be 18°C (65°F) or warmer. (*WARNING: Never use direct heat to warm aerosol cans! Only warm water should be used!*) Apply liberally to area to be lubricated. Wipe off excess.

Sentinel's "S" line of spray lubricants are non-ozone depleting products specially formulated for industry. Sentinel's "S" line contains no CFC's, HCFC's, Methyl chloroform, or any other material known to affect the stratospheric ozone.

TYPICAL CHARACTERISTICS

NLGI Grade	1	ASTM D-1092
Worked Penetration	310-340	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability	-1	ASTM D- 942
Psi Drop @ 100 hrs		
Rust Preventative	1a	ASTM D-1743
No Stain		
Water Washout	1.2	ASTM D-1264
Extreme Pressure	45+ (100)	ASTM D-2509
Timken OK Load Kg (Lb)		
Four Ball Wear	.7mm	ASTM D-2266
Solids	Copper/Bronze	
Appearance	Gold Metallic Tacky	
USDA Classification	H-2	
Net Weight per 20oz Aerosol Can	14.5oz. (411g)	

PIN #

01013

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.

P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240

15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603

PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565

WWW.SENTINELSYNTHETIC.COM