

PRODUCT DATA SHEET



SL WR "S" WHITE WATERPROOF GREASE

PRODUCT DESCRIPTION

SL WR "S" White Grease is an outstanding grease for every phase of lubrication including (but not limited to) in the presence of water steam, most acids, or salts. There is little or no washout, breakdown, or emulsification when subjected to high temperatures.

SL WR "S" White Grease is formulated with materials acceptable to FDA and USDA for use with food handling and food products. It shrugs off beer, alcohol, beverages, salt, starches, jellies, sugar and flour. Even the cleaning chemicals used in food plants have little effect on its lubricating properties. It is recommended for all sides, cams, bearings, and all types of mechanical equipment especially those subjected to water conditions and/or high temperature.

DIRECTIONS: Shake can well before use. Can temperature should be 18°C (65°F) or warmer. (*WARNING: Never use direct heat to warm aerosol cans! Only warm water should be used!*) Insert plastic extender tube for pin point application. Apply liberally to area to be lubricated. Wipe off excess.

Sentinel's "S" line of spray lubricants are non-ozone depleting products specially formulated for industry. Sentinel's "S" line contains no CFC's, HCFC's, Methyl chloroform, or any other material known to affect the stratospheric ozone.

Because of the foregoing, and its white color, SL WR "S" White Grease is highly recommended for food plants, dairies, meat packing houses, bakeries, pharmaceutical plants, hospitals, textile plants, etc.

TYPICAL CHARACTERISTICS

NLGI Grade	2	ASTM D-1092
Worked Penetration	265-295	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability	-1	ASTM D- 942
Psi Drop @ 100 hrs		
Rust Preventative	1a	ASTM D-1743
No Stain		
Water Washout	.5	ASTM D-1264
Extreme Pressure	34+ (75)	ASTM D-2509
Timken OK Load Kg (Lb)		
Four Ball Wear	.6mm	ASTM D-2266
Solids	Zinc Oxide	
Appearance	White Opaque Tacky	
USDA Classification	H-1	
Net Weight per 20oz Aerosol Can	13 oz. (369g)	

PIN #

01015

TO ORDER OR FOR ADDITIONAL INFORMATION

QUALITY WITHOUT QUESTIONS!

SENTINEL LUBRICANTS CORP.

P.O. BOX 69-4240 MIAMI, FLORIDA 33269-1240

15755 NW 15TH AVENUE MIAMI, FLORIDA 33169-5603

PH.(305) 625-6400 (800)842-6400 FAX(305) 625-6565

WWW.SENTINELSYNTHETIC.COM